

FAST CURE ADHESIVE

TECHNICAL DATA SHEET



Product Description

- Industrial grade, highly durable polyether construction adhesive/sealant
- Ready to use, cures in the presence of moisture
- Will not harden, yellow or lose its flexibility
- Superior adhesive strength for construction applications
- Weather resistant, Type II for extended water contact
- UV resistant
- Paintable
- Smooth gunning, workable in low temperatures

Applications

- All-purpose structural adhesive adheres to OSB, wood, EPS foam, concrete, metal, phenolic, most vinyl, PVC, ABS and other non-asphaltic substrates
- Indoor/outdoor use

Package/Colors

- 20-oz sausage pack: White (61007)
- 20-oz sausage pack: Gray (61008)
- 20 count per case
- 45 cases typical pallet

Technical Data

- Specific gravity 1.38- 1.42
- Skin time 30-mins. (77°F, 50% rh)
- Non-sagging
- Tensile strength 350 psi
- Lap shear 325 psi
- Elongation 300%
- Peel adhesion 35 pli
- Hardness Shore A 45-50
- Service temp. -75°F to 350°F
- Non-corrosive, non-staining

Environmental

- 99% solids, no solvents
- No isocyanates
- Low VOC, less than 14-grams/liter
- No hazardous air pollutants (HAPS-free)
- Shelf life of 18-months from indicated date of manufacture when stored below 80°F
- Will not freeze

Engineering Standards

- Meets or exceeds ASTM C920, Type S, Grade NS, Class 25. Use T, NT, G, I and A
- UV stability ASTM G26, (no change at 2,000 UV-A hours)
- USDA compliant

Usage Instructions

- Apply to clean, dry, frost-free surfaces to ensure proper seal
- Application temperature of 0°F to 120°F
- Always check adhesion
- Paintable after cure, always test to ensure suitability
- Use with adequate ventilation, inhalation of vapor during application and cure may cause slight eye and throat irritation
- In case of contact with eyes, lips or mouth flush thoroughly with water. If irritation persists consult a physician
- Avoid repeated, prolonged contact to skin
- Refer to SDS for additional warnings and instructions

Limited Warranty

- Products are free from manufacturing defects and when used according to the manufacturer's published specifications will meet the manufacturer's published performance standards for a period of ten years from the date of shipment from the factory. Sustain will, at its sole option, replace the defective product or refund the purchase price paid by the user. There are no other warranties, expressed or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose. The user is responsible for determining the suitability of the product for the user's needs. Neither Sustain nor its manufacturers shall have a liability for any other damages, including but not limited to any indirect, special or consequential damages, even if they have been advised of the possibility of such.

For More Info

SIPSEAL.COM | INFO@SIPSEAL.COM | (651) 300-0505

Made in USA