

LIQUID FLASHING

TECHNICAL DATA SHEET



Product Description

- Industrial grade, liquid flashing for sealing rough openings and preparing joints for liquid membrane
- Use with *SIP-SEAL Liquid Membrane UV Plus* for a complete, permanently flexible, vapor-permeable weather barrier
- Ready to use, cures in the presence of moisture
- Will not harden, yellow, or lose its flexibility
- UV stable (no change at 2,000 UV-A hours)
- Weather resistant, Type II for extended water contact. Does not absorb water
- Smooth gunning, trowel grade and workable in low temperatures
- Make windows, doors, and other rough openings highly weather resistant while allowing moisture vapor to escape
- Adheres to wood, gypsum, concrete, metal, vinyl, ABS, EPS, poly ISO and polyurethane foam, plus most other non-asphaltic substrates
- Will not leach plasticizers
- Cured product is non-tacky

Technical Data

- Specific gravity 1.38-1.40
- Cure time 24-hours (77°F, 50% RH) 3/16"
- Non-sagging
- Tensile strength D412: 170 psi
- Elongation 250% @ 25mils
- Hardness Shore A 25-30
- High-temp resistance 400°F for brief periods
- Low-temp flexibility -75°F
- E96 Vapor Permeance - >10@25 mils
- Non-corrosive, non-staining
- Nail sealable
- USDA compliant

Package/Colors

- 20-oz sausage pack: Medium Gray
- 20 count per case
- 45 cases per pallet
- Bulk pails available special order

Environmental

- 99% solids, no solvents
- No isocyanates
- Low VOC, less than 14-grams/liter
- No hazardous air pollutants (HAPS-free)
- Shelf life 18-months from date of manufacture when stored below 80°F
- Will not freeze

***Usage
Instructions***

- Apply to clean, dry, frost-free surfaces
- Trowel to 25 mils thickness
- Application temperature of 0°F to 120°F
- Always check adhesion
- Use with adequate ventilation, inhalation of vapor during application and cure may cause slight eye and throat irritation
- In case of contact with eyes, lips, or mouth flush thoroughly with water. If irritation persists, consult a physician. Do not swallow
- Avoid repeated, prolonged contact to skin
- Refer to SDS for additional warnings and instructions
- Contact *SIP-SEAL* for complete installation instructions

Limited Warranty

Products are free from manufacturing defects and when used according to the manufacturer's published specifications will meet the manufacturer's published performance standards for a period of ten years from the date of shipment from the factory. Sustant will, at its sole option, replace the defective product or refund the purchase price paid by the user. There are no other warranties, express or implied, including but not limited to any implied warranties of merchantability or fitness for a particular purpose. The user is responsible for determining the suitability of the product for the user's needs. Neither Sustant nor its manufacturers shall have a liability for any other damages, including but not limited to any indirect, special, or consequential damages, even if they have been advised of the possibility of such.

For More Info:

SIPSEAL.COM | INFO@SIPSEAL.COM | (651) 300-0505

Made in USA